



Bailey of Bristol
2004 Technical Specification

DISCOVERY

RANGER

PAGEANT

SENATOR



Discovery Technical Specification

	Berths	Internal Length	Shipping Length	Overall Width	Overall Height	Internal H'room	Awning Size	Tyre Sizes	MTPLM	MRO	Payload Allowance for Essnt Habltatn Equipment	Payload Allownce for Personal Effects	Payload Allownce for Optional Equipment	Total User Payload
100	4	4.447m 14'7"	6.116m 20'1"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	876cm	185/65 R14 LI90	1124kg 22.1cwt	878kg 17.3cwt	75kg 1.5cwt	121kg 2.4cwt	50kg 1.0cwt	246kg 4.8cwt
200	4	4.631m 15'3"	6.300m 20'7"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	894cm	185/65 R14 LI90	1151kg 22.7cwt	903kg 17.8cwt	75kg 1.5cwt	123kg 2.4cwt	50kg 1.0cwt	248kg 4.9cwt
300	5	4.631m 15'3"	6.300m 20'7"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	894cm	185/65 R14 LI90	1156kg 22.8cwt	899kg 17.7cwt	75kg 1.5cwt	132kg 2.6cwt	50kg 1.0cwt	257kg 5.1cwt
400	5	5.059m 16'7"	6.728m 21'11"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	937cm	195/70 R14 LI96	1213kg 23.9cwt	931kg 18.3cwt	75kg 1.5cwt	147kg 2.9cwt	50kg 1.0cwt	282kg 5.6cwt

A Tolerance in the MRO has been allowed for in the calculations of Payload Margins. The awning length measurement shown is to be interpreted as a guide only and enquiry should be made to individual awning manufacturers to the correct size.

EXTERIOR

- Al-ko galvanised chassis with Euro-axle
- Gas strut assisted handbrake
- 14" wheels with low profile tyres
- Fully insulated walls, floor and roof to grade II classification of EN1645-1 (Panel thickness : Sides 28mm, Ceiling 31mm & Floor 44mm)
- Twin section exterior stable door
- Polyplastic double glazed windows throughout
- Awning light

NEW Longer A-frame for enhanced towing stability
 NEW Full height ABS front panel with high line profile and integral grab handles
 NEW Re-engineered gas bottle locker with improved access and storage
 NEW Full height ABS rear panel with integral light cluster and integral grab handles
 NEW ABS 'Step-Up' A-Frame fairing
 NEW Polyplastic full width 'Panoramic' front window
 NEW Design graphics

- Whale Watermaster water inlet and submersible pump
- Inboard pressurised hot and cold fresh water system with reinforced hosing
- Large bore rigid waste plumbing routed to side of tourer
- Shower unit with ceramic ball mixer tap
- Washroom hand basin with ceramic ball mixer tap
- Fully fitted vanity unit, wall mirror and integral storage

NEW Truma 30 mbr gas regulator

KITCHEN EQUIPMENT

- Spinflo recessed 3-burner hob and grill unit incorporating flush fitting glass hinged lid
- Spinflo recessed enamel sink and drainer with ceramic ball mixer tap
- L-shaped kitchen units with dedicated cutlery and wire basket storage
- Extended worktop surfaces (model specific)

NEW Thetford 77 litre refrigerator with full width freezer compartment

FURNITURE & SOFT FURNISHINGS

- Full size dinette table
- Side dinette occasional table
- Hinged bed box tops for easy access
- Sculpted wooden bunk fall out rails
- Wood effect laminate floor covering

NEW Aircraft style overhead storage lockers
 NEW Co-ordinated fixtures and fittings in satin silver
 NEW Wrap around U-shaped seating
 NEW Standard 'Oasis' soft furnishings with co-ordinating curtains

GENERAL EQUIPMENT

- Flyscreen and sunblind to kitchen window
- Flyscreen and sunblind to saloon roof lights
- Remi Top 'slide and tilt' sun roof with integral ceiling lighting (cost option)

SECURITY

- Selectamark electronic tagging
- Single key operation on all exterior doors
- Vin no. etched to all exterior windows
- Vin no. scribed in chassis member

LUX PACK CONTENTS (cost option)

- Remis Flyscreens and sunblinds to all principal windows
- Remis Upper half exterior door flyscreen
- Loose fit drop-in carpet

BED SIZES

DISCOVERY 100 - Front Saloon 6'8" x 5'10" or 2 @ 5'10" x 2'3", Rear Single 6'8" x 2'2" & O/Head 6'6" x 1'11"
 DISCOVERY 200 - Front Saloon 6'8" x 4'5", Side Single 5'7" x 2'0" & O/Head 5'5" x 1'11"
 DISCOVERY 300 - Front Saloon 6'8" x 5'1", Rear Double 5'11" x 3'9" & O/Head 5'9" x 1'11"
 DISCOVERY 400 - Front Saloon 6'8" x 4'5", Rear O/Side Single 5'11" x 2'0" & O/S O/Head 5'9" x 1'11", Rear N/Side Single 5'7" x 2'2"

ELECTRICAL SYSTEM

- Mains electric with two 230v sockets
- Circular halogen ceiling lighting
- Switch mode battery charger with 12 amps output
- RCD/MCB protection for mains electric system
- 25 metre mains connecting lead

HEATING & WATER SYSTEM

- Truma 3002 3kw heater
- Truma Ultrastore water heater (gas/electric operation)
- Swivel unit Thetford cassette toilet with integrated header tank

Please note that the Remi Top roof light has been re-located to centre of the caravan on the flat roof section for all 2004 models and not the location shown in the photographs.

Whilst every attempt is made within this brochure to accurately reflect and describe our 2004 range of home market tourers (purchased and stored on the mainland and used for leisure purposes) our policy of continued improvement and changes in market and supply conditions means that we reserve the right to alter specifications without further notice. Your Bailey retailer will confirm all specification details prior to you making your purchasing decision. Bailey retailers sell our products of their own choice and not as agents of Bailey. They are therefore unable to bind Bailey or make any representation or undertaking whatsoever on behalf of Bailey Caravans Ltd. Colour reproduction is subject to the limitations of the production process. Some materials used in the production of our tourers can result in a variation to the figures quoted in respect of measurements and weights. All data is calculated using metric weights and measurements. The imperial figures quoted are conversions thereof. The tourers in this brochure conform to the European norms EN1645-1, EN1645-2, EN1648-1, EN1949 & EN721 and to the British Standards for Touring Homes BS5482 (Part II) & BS6765 (Part IV). E & O.E. The touring homes detailed in this brochure are designated by their model year. The model year runs from 1st September to the 31st August. 2004 models are despatched by Bailey to approved retailers from 1st September 2003.

JNB

Ranger Technical Specification

	Berths	Internal Length	Shipping Length	Overall Width	Overall Height	Internal H'room	Awning Size	Tyre Sizes	MTPLM	MRO	Payload Allowance for Essnt Habitain Equipment	Payload Allowance for Personal Effects	Payload Allowance for Optional Equipment	Total User Payload
380/2	2	3.659m 12'0"	5.328m 17'5"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	796cm	185/65 R14 LI90	1043kg 20.5cwt	853kg 16.8cwt	75kg 1.5cwt	93kg 1.8cwt	22kg 0.4cwt	190kg 3.7cwt
460/2	2	4.447m 14'7"	6.116m 20'1"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	875cm	185/65 R14 LI90	1124kg 22.1cwt	926kg 18.2cwt	75kg 1.5cwt	101kg 2.0cwt	22kg 0.4cwt	198kg 3.9cwt
470/4	4	4.631m 15'3"	6.300m 20'7"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	896cm	185/65 R14 LI90	1177kg 23.2cwt	957kg 18.8cwt	75kg 1.5cwt	123kg 2.4cwt	22kg 0.4cwt	220kg 4.3cwt
500/5	5	5.059m 16'7"	6.728m 21'11"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	941cm	195/70 R14 LI96	1265kg 24.9cwt	1031kg 20.3cwt	75kg 1.5cwt	137kg 2.7cwt	22kg 0.4cwt	234kg 4.6cwt
510/4	4	5.059m 16'7"	6.728m 21'11"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	941cm	195/70 R14 LI96	1237kg 24.3cwt	1013kg 19.9cwt	75kg 1.5cwt	127kg 2.5cwt	22kg 0.4cwt	224kg 4.4cwt
510/4L	4	5.059m 16'7"	6.728m 21'11"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	941cm	195/70 R14 LI96	1250kg 24.6cwt	1026kg 20.2cwt	75kg 1.5cwt	127kg 2.5cwt	22kg 0.4cwt	224kg 4.4cwt
550/6	6	5.408m 17'9"	7.077m 23'2"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	976cm	195/70 R14 LI96	1304kg 25.7cwt	1056kg 20.8cwt	75kg 1.5cwt	151kg 3.0cwt	22kg 0.4cwt	248kg 4.9cwt

A Tolerance in the MRO has been allowed for in the calculations of Payload Margins. The awning length measurement shown is to be interpreted as a guide only and enquiry should be made to individual awning manufacturers to the correct size.

EXTERIOR

- Al-ko galvanised chassis with Euro-axle
- Gas strut assisted handbrake
- 14" wheels with low profile tyres
- Fully insulated walls, floor and roof to grade II classification of EN1645-1 (Panel thickness : Sides 28mm, Ceiling 31mm & Floor 44mm)
- Twin section exterior stable door with double glazed window and window blind
- Polyplastic double glazed windows throughout
- Awning light
- Status TV aerial and booster

NEW Long A-Frame for enhanced towing stability
 NEW Full height ABS front panel with high line profile and integral grab handles
 NEW Re-engineered gas bottle locker with improved access and storage
 NEW Full height ABS rear panel with integral light cluster and integral grab handles
 NEW ABS 'Step-Up' A-Frame fairing
 NEW Polyplastic full width 'Panoramic' front window
 NEW Design graphics

ELECTRICAL SYSTEM

- Mains electric with two 230v sockets
- TV station with 230v/12v/aerial sockets
- Circular halogen ceiling lighting
- Switch mode battery charger with 12 amps output
- RCD/MCB protection for mains electric system
- 25 metre mains connecting lead

NEW New style 12v reading lights
 NEW Electrical consumer unit

HEATING & WATER SYSTEM

- Truma 3002 3kw gas heater & supplementary 230v Ultrahat system with silent running night setting
- Truma Ultratherm & blown air distribution system
- Truma Ultrastore water heater (gas/electric operation)

- Swivel unit Theford cassette toilet with integrated header tank
- Whale Watermaster water inlet & submersible pump
- Inboard pressurised hot and cold fresh water system with reinforced hosing
- Large bore rigid waste plumbing routed to side of tourer
- Shower unit with ceramic ball mixer tap
- Single piece circular plastic shower unit (model specific)
- Washroom hand basin with ceramic ball washroom mixer tap
- Fully fitted vanity unit, wall mirrors and integral storage

NEW Truma 30 mbr gas regulator

KITCHEN EQUIPMENT

- Dometic 77 litre refrigerator with full width freezer compartment
- Spinflo recessed 4-burner hob unit incorporating flush fitting glass hinged lid
- Spinflo combined grill and domestic style glass fronted oven plus flame failure device
- Spinflo recessed enamel sink and drainer with ceramic ball mixer tap
- L-shaped kitchen units with dedicated cutlery and wire basket storage
- Extended worktop surfaces (model specific)

FURNITURE & SOFT FURNISHINGS

- Free standing table with dedicated storage
- Side dinette occasional table (model specific)
- Chest of drawers with fold over coffee table (model specific)
- Pull out roller slatted bed
- Aircraft style overhead storage lockers with real wood locker doors
- Hinged bed box slatted tops for easy access
- Sculpted wooden bunk fall out rails
- Fully sprung upholstery (except split cushions used in bunk make up)

NEW Co-ordinated fixtures & fittings in satin silver
 NEW Standard 'Harmony' soft furnishings with co-ordinating lined curtains & scatter cushions
 NEW Loose fit drop-in carpet

GENERAL EQUIPMENT

- Remi Top 'slide and lift' sun roof with integral ceiling lighting
- Remis flyscreen & sunblind to all principal windows
- Remis flyscreen & sunblind to saloon roof lights
- Remis upper half exterior door flyscreen
- Fitted doorwell mat
- Analogue clock

SECURITY

- Selectamark electronic tagging
- Single key operation on all exterior doors
- Vin no. etched to all exterior windows
- Vin no. scribed in chassis member

BED SIZES

RANGER 380/2 - Front Saloon 6'8" x 4'6"
 or 2 @ 6'1" x 2'3"
 RANGER 460/2 - Front Saloon 6'8" x 4'6"
 or 2 @ 6'1" x 2'3"
 RANGER 470/4 - Front Saloon 6'8" x 4'6",
 Side Single 5'7" x 2'0" & O/Head 5'5" x 1'11"
 RANGER 500/5 - Front Saloon 6'8" x 4'3"
 or 2 @ 5'11" x 2'3", Rear Double 6'8" x 4'1"
 & Rear O/Head 5'9" x 1'11"
 RANGER 510/4 - Front Saloon 6'8" x 4'4"
 or 2 @ 5'11" x 2'3", Side Single 5'11" x 2'0"
 & O/Head 5'9" x 1'11"
 RANGER 510/4L - Front Saloon 6'8" x 4'4",
 Side Single 5'11" x 2'0" & O/Head 5'9" x 1'11"
 RANGER 550/6 - Front Saloon 6'8" x 4'1"
 or 1 @ 5'8" x 2'3" & 1 @ 6'1" x 2'3", N/Side Single
 5'7" x 2'0", N/S O/Head Single 5'5" x 1'11",
 Rear Single 4'10" x 1'11", Rear O/Head 4'10" x 1'11"

Please note that the Remi Top roof light has been re-located to centre of the caravan on the flat roof section for all 2004 models and not the location shown in the photographs.

Pageant Technical Specification

	Berths	Internal Length	Shipping Length	Overall Width	Overall Height	Internal H'room	Awning Size	Tyre Sizes	MTPLM	MRO	Payload Allowance for Esstn Habstatn Equipment	Payload Allowance for Personal Effects	Payload Allowance for Optional Equipment	Total User Payload
MAJESTIC	2	4.115m 13'6"	5.810m 19'1"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	828cm	185/65 R14 LI90	1135kg 22.3cwt	960kg 18.9cwt	75kg 1.5cwt	97kg 1.9cwt	3kg 0.1cwt	175kg 3.4cwt
MONARCH	2	4.731m 15'6"	6.390m 20'12"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	889cm	195/70 R14 LI96	1208kg 23.8cwt	1027kg 20.2cwt	75kg 1.5cwt	103kg 2.0cwt	3kg 0.1cwt	181kg 3.6cwt
AUVERGNE	5	5.258m 17'3"	6.920m 22'9"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	942cm	195/70 R14 LI96	1338kg 26.3cwt	1121kg 22.1cwt	75kg 1.5cwt	139kg 2.7cwt	3kg 0.1cwt	217kg 4.3cwt
CHAMPAGNE	4	5.258m 17'3"	6.920m 22'9"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	942cm	195/70 R14 LI96	1302kg 25.6cwt	1095kg 21.6cwt	75kg 1.5cwt	129kg 2.5cwt	3kg 0.1cwt	207kg 4.1cwt
LOIRE	4	5.258m 17'3"	6.920m 22'9"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	942cm	195/70 R14 LI96	1313kg 25.8cwt	1106kg 21.8cwt	75kg 1.5cwt	129kg 2.5cwt	3kg 0.1cwt	207kg 4.1cwt
MOSELLE	4	5.258m 17'3"	6.920m 22'9"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	942cm	195/70 R14 LI96	1285kg 25.3cwt	1078kg 21.2cwt	75kg 1.5cwt	129kg 2.5cwt	3kg 0.1cwt	207kg 4.1cwt
BORDEAUX	4	5.258m 17'3"	6.920m 22'9"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	942cm	195/70 R14 LI96	1345kg 26.5cwt	1123kg 22.1cwt	75kg 1.5cwt	129kg 2.5cwt	18kg 0.4cwt	222kg 4.4cwt
VENDEE	4	5.508m 18'1"	7.210m 23'8"	2.19m 7'2"	2.71m 8'10"	1.90m 6'3"	967cm	195/70 R14 LI96	1321kg 26.0cwt	1112kg 21.9cwt	75kg 1.5cwt	131kg 2.6cwt	3kg 0.1cwt	209kg 4.1cwt

A Tolerance in the MRO has been allowed for in the calculations of Payload Margins. The awning length measurement shown is to be interpreted as a guide only and enquiry should be made to individual awning manufacturers to the correct size.

EXTERIOR

- Al-ko galvanised chassis with Euro-axle
- Gas strut assisted handbrake
- 14" wheels with low profile tyres
- Al-ko chassis mounted spare wheel carrier and spare wheel
- Fully insulated walls, floor and roof to grade II classification of EN1645-I (Panel thickness: Sides 28mm, Ceiling 31mm & Floor 44mm)
- Twin section exterior stable door with double glazed window and window blind
- Polyplastic double glazed windows throughout
- Full height ABS front panel with high line profile and integral grab handles
- Re-engineered gas bottle locker with improved access and storage
- Full height ABS rear panel with twin high level brake lights
- Wrap around rear light clusters with integral warning triangle
- Reinforced plastic rear grab handles
- Awning light
- Status TV aerial and booster

NEW Al-ko AKS 2004 stabiliser

ELECTRICAL SYSTEM

- Mains electric with three 230v sockets
- TV station with 230v/12v/aerial sockets
- 12v and 230v reading lights
- 230v light dimmer switch
- Circular halogen ceiling lighting
- Flush fit halogen downlighters
- Switch mode battery charger with 20 amps output
- RCD/MCB protection for mains electric system
- 25 metre mains connecting lead

HEATING & WATER SYSTEM

- Truma 3002 3kw gas heater & supplementary 230v Ultraheat system with silent running night setting
- Truma Ultratherm & blown air distribution system
- Truma Ultrastore water heater (gas/electric operation)

- Swivel Theiford cassette toilet with integrated header tank
- Whale Watermaster water inlet with in-line filter and submersible pump
- Inboard pressurised hot and cold fresh water system with reinforced hosing
- Large bore rigid waste plumbing routed to side of tourer
- Shower unit with ceramic ball mixer tap
- Single piece circular plastic shower unit (model specific)
- Washroom hand basin with ceramic ball mixer tap
- Fully fitted vanity unit, wall mirrors & integral storage

NEW Truma 30 mbr gas regulator

KITCHEN EQUIPMENT

- Theiford 86 litre refrigerator with electronic ignition and full width freezer compartment
- Spinflo recessed 4-burner hob unit incorporating flush fitting glass hinged lid
- Spinflo combined grill & domestic style glass fronted oven with electronic ignition and flame failure device
- Spinflo recessed enamel sink and drainer incorporating flush fitting glass hinged lid with ceramic ball mixer tap
- L-shaped kitchen units with dedicated cutlery and wire basket storage
- Extended worktop surfaces covered in a co-ordinating laminate (model specific)

FURNITURE & SOFT FURNISHINGS

- Free standing table with dedicated storage
- Side dinette occasional table (model specific)
- Chest of drawers with fold over coffee table (model specific)
- Aircraft style overhead storage lockers with real wood locker doors and domestic style metal hinges
- Pull out roller slatted bed
- Hinge sprung slatted bed box tops for easy access
- Drop down flaps on large bed box fronts
- Sculpted wooden bunk fall out rails

- Fully sprung upholstery (except split cushions used in bunk make up)
- Standard 'Ascal' soft furnishings with co-ordinating lined curtains, pelmet covers, bolster and scatter cushions
- Optional 'Newbury' soft furnishings with co-ordinating lined curtains, pelmet covers, bolster and scatter cushions
- Fully fitted deep pile co-ordinated carpet

GENERAL EQUIPMENT

- Remi Top 'slide and tilt' sun roof with integral ceiling lighting
- Omnivert dual action rooftop mounted extractor fan
- Remis flyscreen & sunblinds to all principal windows
- Remis flyscreen & sunblind to 4 way rooflight in saloon
- Remis full length flyscreen to exterior door
- Fitted doorwell mat
- Analogue clock

SECURITY

- Selectamark electronic tagging
- Single key operation on all exterior doors
- Vin no. etched to all exterior windows
- Vin no. scribed in chassis member

BED SIZES

MAJESTIC & MONARCH - Front Saloon 6'8" x 4'7" or 2 @ 6'2" x 2'3"

AUVERGNE - Front Saloon 6'8" x 4'7" or 2 @ 6'2" x 2'3", Rear Double 6'8" x 4'4" & Rear O/Head 5'9" x 1'11"

CHAMPAGNE & LOIRE - Front Saloon 6'8" x 4'7" or 1 @ 6'2" x 2'3" & 1 @ 5'10" x 2'3", O/Side Single 5'11" x 2'0" & O/Head Single 5'9" x 1'11"

MOSELLE - Front Saloon 6'8" x 4'4", O/Side Single 5'11" x 2'0" & O/Head Single 5'9" x 1'11"

BORDEAUX - Front Saloon 6'8" x 5'4", Rear Double 6'4" x 4'6"

VENDEE - Front Saloon 6'8" x 4'4", Rear Double 6'3" x 4'6"

TNB

Please note that the Remi Top roof light has been re-located to centre of the caravan on the flat roof section for all 2004 models and not the location shown in the photographs.



Bailey of Bristol Warranty Cover

Total customer satisfaction is top priority at Bailey and the quality ethos extends to the aftersales service and manufacturer's warranty that comes with every new Bailey touring caravan. In this way we not only ensure long-term peace of mind but also enhance the resale value of your investment. This cover is available at no extra cost to the customer.

6 Year Body Shell Integrity Guarantee

All Bailey products are covered by a six year Body Shell Integrity Guarantee. Cover extends to the following items

Body Leaks & Delamination; water ingress through any permanently sealed seam and joints or delamination of panels and floor, being part of the original manufacturer's construction.

3 Year Manufacturers Warranty

For a period of 12 months from the date of purchase Bailey of Bristol offer a comprehensive warranty on all parts and components as well as full coverage for any manufacturing faults.

The 2nd & 3rd year of cover extends to these items:

Chassis; all chassis members including outriggers.

Suspension; springs, hangers, shackle pins, bushes, shock absorbers and mountings.

Running Gear; axles, hubs, hub bearings, hub oil seals, road wheels (excluding tyres and tubes).

Braking Systems; all mechanical linkage, backing plates, actuators, drums and shoes, (Exclusions: this warranty does not cover damage to brake drums, shoes or any faults caused through misuse of the braking system or normal wear and tear).

Towing Mechanism; all mechanical components fitted to tourers (excluding electrics).

Cooker; the cooker unit including burners, grill, oven and flame failure device and igniter.

Fridge; door seal, condenser, gas control valve, gas igniter, flame failure device, 12 and 230v heater elements, gas thermostat, 230v thermostat, 230v temperature control switch.

Water System; water heater (gas or electric), fresh water tank, water pump, water gauges, taps and shower head.

Auxiliary Electrics; mains hook-up input connector, ELCB, battery charger and distributor unit, interior lighting units (excluding bulbs).

Cassette Toilet; the cassette toilet is covered (excluding seals, valves and glands).

Heating System; thermostat, motor, switches, control unit, gas heater, flame failure device, igniter (excluding ducting and fittings).

An additional 4th & 5th year extension to the Manufacturers Warranty is also available, please ask your Bailey retailer for more information

In the unusual event of something going wrong then your first contact should always be your supplying retailer. Approved Bailey agents enjoy a first class after sales support service from the manufacturer and they should be able to offer all the help you need to rectify any problems that may exist.

Terms and Conditions

The above offer is subject to the following conditions. The warranty agreement does not affect the purchaser's statutory rights.

The Bailey Warranty Cover is offered subject to the following simple conditions: 1. The duration of the Body Shell Integrity Guarantee is 72 months from the date of purchase and the duration of the Manufacturers Warranty is 36 months from the date of purchase. 2. That an authorised Bailey Service Centre has carried out a full service, including moisture survey, annually from the date of purchase as new (or within 6 weeks of each anniversary of purchase). 3. This agreement is personal to the purchaser of the tourer as new from an authorised Bailey retailer or authorised representative and is not transferable by way of assignment, novation or otherwise. 4. That the seams and panels requiring repair are part of the original construction of the tourer and have not been tampered with or repaired otherwise than by Bailey Caravans Limited or an authorised Bailey Service Centre. 5. That original VAT invoices be retained as proof those annual inspections have been carried out. 6. That in the event of any repairs being identified as being necessary during the course of an annual inspection the tourer is made available to an authorised Bailey Service Centre or Bailey Caravans Limited within 6 weeks for the purpose of carrying out the repair work. 7. No repairs, including the fitting of any replacement unit, may be undertaken or commenced under the terms of the agreement unless authorisation is obtained by an authorised Bailey Service Centre from Bailey Caravans Limited. No liability will exist with regard to any claims not authorised in this way. 8. Bailey Caravans Limited reserve the right to examine the tourer before any repairs commence or any replacement part fitted. 9. No liability will be accepted for damage caused by neglect, corrosion, intrusion of foreign or deleterious matter, lack of servicing, over-heating, freezing or abuse or the continued use of the tourer after a fault has become evident or for the consequential loss or damage to parts not covered by this agreement. 10. That tourers covered by this agreement shall not be put out to hire, reward or any other commercial use in any timed competition race. 11. That the tourer shall be used only for its ordinary and intended purpose and shall not be subjected to any treatment or conditions which could reasonably be foreseen to cause or result in damage to the tourer or excessive wear and tear. 12. That the tourer registration card shall have been sent to Bailey Caravans Limited within 6 weeks of its purchase as new. 13. That private cars, or 4x4 type vehicles substituting as private cars, shall have only towed the tourer. 14. Bailey Caravans Limited's liability under this agreement shall be limited to supplying labour and materials of a value not exceeding £2,500 including VAT in respect of each claim or series of claims. No liability arises out of this agreement for consequential costs or damage or for repair costs (other than labour materials). 15. No liability will be accepted for any accidental or fire damage or any losses incurred by accident or fire. 16. No liability will be accepted for transport costs to and from point of repair or consequential cost relating to transportation. 17. No liability of any kind exists in respect of third parties or bodily injury.

www.bailey-caravans.co.uk

South Liberty Lane, Bristol BS3 2SS, England