

Coachman Caravan Company Limited
Amsterdam Road
Sutton Fields Industrial Estate
Hull HU7 0XF

Telephone: 01482 839737
Fax: 01482 878143
Email: sales@coachman.co.uk
Aftercare Telephone: 01482 877405
Aftercare Email: aftercare@coachman.co.uk

the journey starts here



www.coachman.co.uk



This brochure has been designed to provide you with basic information prior to making a purchase decision. Please refer to your dealer for additional information before you buy.

Coachman Caravan Company Limited reserves the right to alter technical specifications, prices and model ranges as materials and conditions demand and can accept no responsibility for discrepancies between these and subsequent models. Household items illustrated in the brochure (e.g. fruit and personal effects) have been used to enhance photography and are not supplied with the caravan. Limitations in the printing process may mean colours are not truly represented.

It should be noted that distributors and dealers are not the agents of Coachman Caravan Company Limited and therefore are not authorised to bind the Company by any specific or implied undertaking or representation.

Please note: Touring caravans are designated by the model year. The model year runs from the 1st September to the 31st August: for example a 2012 year model would have been despatched by the manufacturer no earlier than the 15th August, 2011.

Please note: the method of calculating the MRO and payload figures has recently changed. Allowances for essential equipment (e.g. gas cylinders) previously allowed for in the user payload are now within the MRO. The provision for a leisure battery has been included within the personal effects payload allowances.

All Coachman models have been certified by the National Caravan Council for compliance with stringent European Standards, British Legislation and industry set Codes of Practice, specifically relating to health and safety issues. The approval process covers the testing and inspection of critical areas of the product from fire safety, weights and dimensions to gas, electrics and ventilation. Every Coachman caravan carries the "NCC Approved Caravan" badge. The NCC also conducts unannounced inspections at the Coachman factory to ensure continued compliance.

NCC Approval gives you peace of mind that your caravan is legal and safe.

The tow cars used in this brochure are for illustration purposes only.

As the owner of a Coachman caravan, you will be automatically entitled to join our Owners' Club. For more information about the Club, please contact: The Membership Officer, Coachman Owners' Club, 49 Regency Gardens, Yardley Wood, Birmingham, B14 4JS or visit their website: www.coachmanclub.co.uk

Photography: www.markkennett.com



Designed and produced by: www.bluestormdesign.co.uk

Coachman Specifications 2012



the journey starts here





Technical Specifications 2012



Technical Specifications 2012

Model	640/4	655/6
Number of Berths	4	6
Interior Length	6215 mm / 20' 5"	6215 mm / 20' 5"
Shipping Length	7870 mm / 25' 10"	7870 mm / 25' 10"
Overall Width	2320 mm / 7' 7"	2320 mm / 7' 7"
Overall Height (inc T.V Aerial)	2685 mm / 8' 10"	2685 mm / 8' 10"
Maximum Headroom	1955 mm / 6' 5"	1955 mm / 6' 5"
Interior Width	2170 mm / 7' 1"	2170 mm / 7' 1"
Wheel Rim	5.5J x 14	5.5J x 14
Tyre Size	185/70 R14 88	185/70 R14 88
Tyre Pressure (at quoted MTPLM)	2.4 bar / 35 psi	2.4 bar / 35 psi
Bed Sizes	1 x Single 1780 mm x 740 mm (5' 10" x 2' 5")	2 x Single 1880 mm x 740 mm (6' 2" x 2' 5")
Option 1	1 x Single 1600 mm x 740mm (5' 3" x 2' 5") 1 x Double 1880 mm x 1370 mm (6' 2" x 4' 6")	2 x Single 1750 mm x 700 mm (5' 9" x 2' 4") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
Bed Sizes	1 x Double 2080 mm x 1370 mm (6' 10" x 4' 6")	1 x Double 2080 mm x 1450 mm (6' 10" x 4' 9")
Option 2	1 x Double 1880 mm x 1370 mm (6' 2" x 4' 6")	1 x Double 2010 mm x 1320 mm (6' 7" x 4' 4") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
M.T.P.L.M	1840 kg / 36.2cwt	1900 kg / 37.4 cwt
Mass in Running Order	1681 kg / 33.1cwt	1721 kg / 33.9 cwt
Personal Payload	159 kg / 3.1 cwt	179 kg / 3.5 cwt
Options Payload	0 kg / 0 cwt	0 kg / 0 cwt
Total / Maximum User Payload	159 kg / 3.1 cwt	179 kg / 3.5 cwt
Maximum Hitch Weight	100 kg / 1.9 cwt	100 kg / 1.9 cwt
Empty Noseweight	58 kg / 1.1 cwt	47 kg / 0.9 cwt
Awning Size	1070 cm	1070 cm



Model	460/2	520/4	545/4	560/4
Number of Berths	2	4	4	4
Interior Length	4852 mm / 15' 11"	5540 mm / 18' 2"	5800 mm / 19' 0"	5800 mm / 19' 0"
Shipping Length	6507 mm / 21' 4"	7195 mm / 23' 7"	7455 mm / 24' 6"	7455 mm / 24' 6"
Overall Width	2320 mm / 7' 7"	2320 mm / 7' 7"	2320 mm / 7' 7"	2320 mm / 7' 7"
Overall Height (inc T.V Aerial)	2685 mm / 8' 10"	2685 mm / 8' 10"	2685 mm / 8' 10"	2685 mm / 8' 10"
Maximum Headroom	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"
Interior Width	2170 mm / 7' 1"	2170 mm / 7' 1"	2170 mm / 7' 1"	2170 mm / 7' 1"
Wheel Rim	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15
Tyre Size	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104
Tyre Pressure (at quoted MTPLM)	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi
Bed Sizes	2 x Single	2 x Single	1 x Single	1 x Single
Option 1	1880 mm x 760 mm (6' 2" x 2' 6")	1880 mm x 760 mm (6' 2" x 2' 6") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760mm x 610 mm (5' 9" x 2' 0")	1600 mm x 760 mm (5' 3" x 2' 6") 1 x Single 1580 mm x 760 mm (5' 2" x 2' 6") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	1650 mm x 760 mm (5' 5" x 2' 6") 1 x Single 1570 mm x 760 mm (5' 2" x 2' 6") 1 x Double 1880 mm x 1370 mm (6' 2" x 4' 6")
Bed Sizes	1 x Double	1 x Double	1 x Double	1 x Double
Option 2	2110 mm x 1470 mm (6' 11" x 4' 10")	2110 mm x 1470 mm (6' 11" x 4' 10") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2110 mm x 1160 mm (6' 11" x 3' 10") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	2110 mm x 1160 mm (6' 11" x 3' 10") 1 x Double 1880 mm x 1370 mm (6' 2" x 4' 6")
M.T.P.L.M	1450 kg / 28.5 cwt	1585 kg / 31.2 cwt	1625 kg / 32 cwt	1645 kg / 32.4 cwt
Mass in Running Order	1324 kg / 26.1 cwt	1433 kg / 28.2 cwt	1470 kg / 28.9 cwt	1490 kg / 29.3 cwt
Personal Payload	126 kg / 2.5 cwt	152 kg / 3 cwt	155 kg / 3.1 cwt	155 kg / 3.1 cwt
Options Payload	0 kg / 0 cwt	0 kg / 0 cwt	0 kg / 0 cwt	0 kg / 0 cwt
Total / Maximum User Payload	126 kg / 2.5 cwt	152 kg / 3 cwt	155 kg / 3.1 cwt	155 kg / 3.1 cwt
Maximum Hitch Weight	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt
Empty Noseweight	51 kg / 1.1 cwt	54 kg / 1.1 cwt	67 kg / 1.7 cwt	44 kg / 1.3 cwt
Awning Size	938 cm	1004 cm	1038 cm	1038 cm



Technical Specifications 2012



Technical Specifications 2012

Model	460/2	470/2	520/4	545/4	560/4
Number of Berths	2	2	4	4	4
Interior Length	4852 mm / 15' 11"	4970 mm / 16' 4"	5540 mm / 18' 2"	5800 mm / 19' 0"	5800 mm / 19' 0"
Shipping Length	6507 mm / 21' 4"	6625 mm / 21' 9"	7195 mm / 23' 7"	7455 mm / 24' 6"	7455 mm / 24' 6"
Overall Width	2320 mm / 7' 7"	2320 mm / 7' 7"	2320 mm / 7' 7"	2320 mm / 7' 7"	2320 mm / 7' 7"
Overall Height (inc T.V Aerial)	2685 mm / 8' 10"	2685 mm / 8' 10"	2685 mm / 8' 10"	2685 mm / 8' 10"	2685 mm / 8' 10"
Maximum Headroom	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"
Interior Width	2170 mm / 7' 1"	2170 mm / 7' 1"	2170 mm / 7' 1"	2170 mm / 7' 1"	2170 mm / 7' 1"
Wheel Rim	5.5J x 14	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15
Tyre Size	185 R14 102	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104
Tyre Pressure (at quoted MTPLM)	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi
Bed Sizes	2 x Single	2 x Single	2 x Single	1 x Single	1 x Single
Option 1	1880 mm x 760 mm (6' 2" x 2' 6")	1880 mm x 760 mm (6' 2" x 2' 6")	1880 mm x 760 mm (6' 2" x 2' 6") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1600 mm x 760 mm (5' 3" x 2' 6") 1 x Single 1580 mm x 760 mm (5' 2" x 2' 6") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	1650 mm x 760 mm (5' 5" x 2' 6") 1 x Single 1570 mm x 760 mm (5' 2" x 2' 6") 1 x Double 1880 mm x 1370 mm (6' 2" x 4' 6")
Bed Sizes	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double
Option 2	2110 mm x 1470 mm (6' 11" x 4' 10")	2110 mm x 1470 mm (6' 11" x 4' 10")	2110 mm x 1470 mm (6' 11" x 4' 10") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2110 mm x 1160 mm (6' 11" x 3' 10") 1 x Double 1830 mm x 1380 mm (6' 0" x 4' 6")	2110 mm x 1160 mm (6' 11" x 3' 10") 1 x Double 1880 mm x 1370 mm (6' 2" x 4' 6")
M.T.P.L.M	1435 kg / 28.2 cwt	1455 kg / 28.6 cwt	1585 kg / 31.2 cwt	1625 kg / 32 cwt	1630 kg / 32.1 cwt
Mass in Running Order	1305 kg / 25.7 cwt	1324 kg / 26.1 cwt	1428 kg / 28.1 cwt	1465kg / 28.8 cwt	1470 kg / 28.9 cwt
Personal Payload	125 kg / 2.5 cwt	126 kg / 2.5 cwt	152 kg / 3 cwt	155 kg / 3.1 cwt	155 kg / 3.1 cwt
Options Payload	5 kg / 0.1 cwt	5 kg / 0.1 cwt	5 kg / 0.1 cwt	5 kg / 0.1 cwt	5 kg / 0.1 cwt
Total / Maximum User Payload	130 kg / 2.6 cwt	131 kg / 2.6 cwt	157 kg / 3.1 cwt	160 kg / 3.1 cwt	160 kg / 3.1 cwt
Maximum Hitch Weight	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt
Empty Noseweight	51 kg / 1.1 cwt	56 kg / 1.1 cwt	54 kg / 1.1 cwt	64 kg / 1.3 cwt	39 kg / 0.8 cwt
Awning Size	938 cm	950 cm	1004 cm	1038 cm	1038 cm

Model	380/2	450/2	520/4	550/5	560/4	570/6	640/6	655/6
Number of Berths	2	2	4	5	4	6	6	6
Interior Length	4023 mm / 13' 2"	4725 mm / 15' 6"	5478 mm / 18' 0"	5670 mm / 18' 7"	5850 mm / 19' 2"	5850 mm / 19' 2"	6221 mm / 20' 5"	6221 mm / 20' 5"
Shipping Length	5683 mm / 18' 8"	6385 mm / 20' 11"	7138 mm / 23' 5"	7330 mm / 24' 1"	7510 mm / 24' 8"	7510 mm / 24' 8"	7881 mm / 25' 10"	7881 mm / 25' 10"
Overall Width	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"	2260 mm / 7' 5"
Overall Height (inc T.V Aerial)	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2672 mm / 8' 9"	2660 mm / 8' 9"	2660 mm / 8' 9"
Maximum Headroom	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"	1955 mm / 6' 5"
Interior Width	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"	2110 mm / 6' 11"
Wheel Rim	5.5J x 14	5.5J x 14	5.5J x 14	6.0J x 15	6.0J x 15	6.0J x 15	5.5J x 14	5.5J x 14
Tyre Size	175 R14 99	185 R14 102	185 R14 102	195/70 R15 104	195/70 R15 104	195/70 R15 104	185/70 R14 88	185/70 R14 88
Tyre Pressure (at quoted MTPLM)	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi	4.5 bar / 65 psi	2.4 bar / 35 psi	2.4 bar / 35 psi
Bed Sizes	2 x Single	2 x Single	2 x Single	2 x Single	1 x Single	2 x Single	2 x Single	2 x Single
Option 1	1860 mm x 740 mm (6' 1" x 2' 5")	1860 mm x 740 mm (6' 1" x 2' 5")	1860 mm x 740 mm (6' 1" x 2' 5") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	1860 mm x 740 mm (6' 1" x 2' 5") 1 x Single 2030mm x 1390 mm (6' 8" x 4' 7") 1 x Single Bunk 1950 mm x 610 mm (6' 5" x 2' 0")	1540 mm x 740 mm (5' 1" x 2' 5") 1 x Single 1640 mm x 740 mm (5' 4" x 2' 5") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	1740 mm x 740 mm (5' 9" x 2' 5") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0") 2 x Single Bunks 1740 mm x 620 mm (5' 9" x 2' 0")	1860 mm x 740 mm (6' 1" x 2' 5") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0") 2 x Single Bunks 1740 mm x 620 mm (5' 9" x 2' 0")	1860 mm x 740 mm (6' 1" x 2' 5") 1 x Single (rear) 1780 mm x 700 mm (5' 10" x 2' 4") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
Bed Sizes	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double	1 x Double
Option 2	2030 mm x 1440 mm (6' 8" x 4' 9")	2030 mm x 1440 mm (6' 8" x 4' 9")	2030 mm x 1440 mm (6' 8" x 4' 9") 1 x Single 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1760 mm x 610 mm (5' 9" x 2' 0")	2030 mm x 1440 mm (6' 8" x 4' 9") 1 x Double 2030 mm x 1390 mm (6' 8" x 4' 7") 1 x Single Bunk 1950 mm x 610 mm (6' 5" x 2' 0")	2030 mm x 1220 mm (6' 8" x 4' 0") 1 x Double 1900 mm x 1320 mm (6' 3" x 4' 4")	2030 mm x 1320 mm (6' 8" x 4' 4") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0") 2 x Single Bunks 1740 mm x 620 mm (5' 9" x 2' 0")	2030 mm x 1440 mm (6' 8" x 4' 9") 1 x Single (rear) 1830 mm x 720 mm (6' 0" x 2' 4") 1 x Single Bunk 1770 mm x 610 mm (5' 10" x 2' 0") 2 x Single Bunks 1740 mm x 620 mm (5' 9" x 2' 0")	2030 mm x 1440 mm (6' 8" x 4' 9") 1x Double 1980 mm x 1340 mm (6' 6" x 4' 5") 2 x Single Bunks 1700 mm x 610 mm (5' 7" x 2' 0")
M.T.P.L.M	1195 kg / 23.5 cwt	1335 kg / 26.3 cwt	1490 kg / 29.3 cwt	1580 kg / 31.1 cwt	1555 kg / 30.6 cwt	1595 kg / 31.4 cwt	1700 kg / 33.5 cwt	1740 kg / 34.3 cwt
Mass in Running Order	1067 kg / 21 cwt	1200 kg / 23.6 cwt	1328 kg / 26.1 cwt	1406 kg / 27.7 cwt	1389 kg / 27.3 cwt	1409 kg / 27.7 cwt	1510 kg / 29.7 cwt	1550 kg / 30.5 cwt
Personal Payload	118 kg / 2.3 cwt	125 kg / 2.5 cwt	152 kg / 3 cwt	164 kg / 3.2 cwt	156 kg / 3.1 cwt	176 kg / 3.5 cwt	180 kg / 3.5 cwt	180 kg / 3.5 cwt
Options Payload	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt	10 kg / 0.2 cwt
Total / Maximum User Payload	128 kg / 2.5 cwt	135 kg / 2.7 cwt	162 kg / 3.2 cwt	174 kg / 3.4 cwt	166 kg / 3.3 cwt	186 kg / 3.7 cwt	190 kg / 3.7 cwt	190 kg / 3.7 cwt
Maximum Hitch Weight	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt	100 kg / 1.9 cwt
Empty Noseweight	45 kg / 0.6 cwt	52 kg / 1 cwt	54 kg / 1.1 cwt	50 kg / 1 cwt	43 kg / 0.8 cwt	57 kg / 1.1 cwt	42 kg / 0.8 cwt	58 kg / 1.1 cwt
Awning Size	840 cm	913 cm	992 cm	1010 cm	1024 cm	1024 cm	1065 cm	1065 cm

1. The method of calculating the MRO and payload figures has recently changed. Allowances for essential equipment (e.g. gas cylinders) previously allowed for in the user payload are now within the MRO. The provision for a leisure battery has been included within the personal effects payload allowances.

2. Imperial conversions are approximate.

3. Awning dimensions represent the shortest ground to ground awning measurements for 2011 model year Coachman caravans. We do however strongly recommend that you consult your awning supplier before making a purchase as awning manufacturers have different methods of sizing their products.